

# Air Random Orbital Sander

Designed for sanding feather edging and metal finish

# Air Random Orbital Sander

Designed for sanding feather edging and metal finish

8055N



5" Composite Air Sander (Non-Vacuum)

Free Speed	12,000 RPM
Pad Size	125mm / 5"
Orbit Diameter	2.5mm or 5mm / 3/32" or 3/16"
Spindle Thread Size	5/16"-24UNF
Ave. Air Consumption	2.5CFM (70.8 L/min)
Length	155mm (6.1in.)
Net Weight	0.67kg [1.5lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm <sup>2</sup> ]

8053



3" Composite Air Sander

Free Speed	12,000 RPM
Pad Size	75mm / 3"
Orbit Diameter	2.5mm or 5mm / 3/32" or 3/16"
Spindle Thread Size	5/16"-24UNF
Ave. Air Consumption	2.5CFM (70.8 L/min)
Length	155mm (6.1in.)
Net Weight	0.67kg [1.5lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm <sup>2</sup> ]

8055S



5" Composite Air Sander (Self-Vacuum)

Free Speed	12,000 RPM
Pad Size	125mm / 5"
Orbit Diameter	2.5mm or 5mm / 3/32" or 3/16"
Spindle Thread Size	5/16"-24UNF
Ave. Air Consumption	2.5CFM (70.8 L/min)
Length	215mm (8.5in.)
Net Weight	0.87kg [1.9lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm <sup>2</sup> ]

8350



Composite Air Delta Sander

Free Speed	10,000 RPM
Pad Size	Triangle
Orbit Diameter	2.5mm / 3/32"
Ave. Air Consumption	5CFM (141.6 L/min)
Length	180mm (7.1in.)
Net Weight	0.8kg [1.8lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm <sup>2</sup> ]

8056C



6" Composite Air Sander (Central-Vacuum)

Free Speed	12,000 RPM
Pad Size	150mm / 6"
Orbit Diameter	2.5mm or 5mm / 3/32" or 3/16"
Spindle Thread Size	5/16"-24UNF
Ave. Air Consumption	2.5CFM (70.8 L/min)
Length	215mm (8.5in.)
Net Weight	0.87kg [1.9lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm <sup>2</sup> ]

8450



Composite Air Jitterbug Sander

Free Speed	10,000 RPM
Pad Size	100x110mm
Orbit Diameter	2.5mm / 3/32"
Ave. Air Consumption	5CFM (141.6 L/min)
Length	180mm (7.1in.)
Net Weight	0.8kg [1.8lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm <sup>2</sup> ]