

Air Impact Wrench Series

3/8" or 1/2" stubby in confined space

Air Impact Wrench Series

3/8" or 1/2" for general repair work

6310



3/8" Air Impact Wrench

Free Speed	6,500 RPM
Clutch	Jumbo Hammer
Max. Torque	250Ft-lbs. (339Nm)
Bolt Capacity	9/16" (14mm)
Ave. Air Consumption	4.5CFM (127.4 L/min)
Length	245mm (9.6 in.)
Net Weight	3.1kg [6.8lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

6311



1/2" Air Impact Wrench

Free Speed	6,500 RPM
Clutch	Jumbo Hammer
Max. Torque	300Ft-lbs. (407Nm)
Bolt Capacity	9/16" (14mm)
Ave. Air Consumption	4.5CFM (127.4 L/min)
Length	245mm (9.6 in.)
Net Weight	3.1kg [6.8lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

6312



3/8" Air Impact Wrench

Free Speed	6,500 RPM
Clutch	Jumbo Hammer
Max. Torque	250Ft-lbs. (339Nm)
Bolt Capacity	9/16" (14mm)
Ave. Air Consumption	4.5CFM (127.4 L/min)
Length	248mm (9.8 in.)
Net Weight	3.1kg [6.8lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

6313



1/2" Air Impact Wrench

Free Speed	6,500 RPM
Clutch	Jumbo Hammer
Max. Torque	300Ft-lbs. (407Nm)
Bolt Capacity	9/16" (14mm)
Ave. Air Consumption	4.5CFM (127.4 L/min)
Length	248mm (9.8 in.)
Net Weight	3.1kg [6.8lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

6314



1/2" Air Impact Wrench

Free Speed	9,000 RPM
Clutch	Twin Hammer
Working Torque (5s)	750Ft-lbs. (1,016Nm)
Max. Torque (15s)	800Ft-lbs. (1,085Nm)
Bolt Capacity	3/4" (18mm)
Ave. Air Consumption	5CFM (141.6 L/min)
Length	138mm (5.4 in.)
Net Weight	1.8kg [4.0lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

6315



1/2" Air Impact Wrench

Free Speed	9,500 RPM
Clutch	Jumbo Hammer
Working Torque (5s)	450Ft-lbs. (610Nm)
Max. Torque (15s)	500Ft-lbs. (678Nm)
Bolt Capacity	5/8" (16mm)
Ave. Air Consumption	5CFM (141.6 L/min)
Length	109mm (4.3 in.)
Net Weight	1.3kg [2.9lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]