

Air Impact Wrench Series

3/8" or 1/2" stubby in confined space

Air Impact Wrench Series

3/8" or 1/2" for general repair work

6316



3/8" Air Impact Wrench

Free Speed	11,000 RPM
Clutch	Twin Hammer
Working Torque (5s)	330Ft-lbs. (380Nm)
Max. Torque (15s)	450Ft-lbs. (610Nm)
Bolt Capacity	5/8" (16mm)
Ave. Air Consumption	4.3CFM (122.0 L/min)
Length	108mm (4.3in.)
Net Weight	1.42kg [3.12lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

6319



1/2" Air Impact Wrench

Free Speed	12,000 RPM
Clutch	Twin Hammer
Working Torque (5s)	420Ft-lbs. (569Nm)
Max. Torque (15s)	650Ft-lbs. (880Nm)
Bolt Capacity	5/8" (16mm)
Ave. Air Consumption	4.3CFM (122.0 L/min)
Length	99mm (3.9in.)
Net Weight	1.4kg [3.1lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

6317



1/2" Air Impact Wrench

Free Speed	11,000 RPM
Clutch	Twin Hammer
Working Torque (5s)	380Ft-lbs. (515Nm)
Max. Torque (15s)	500Ft-lbs. (678Nm)
Bolt Capacity	5/8" (16mm)
Ave. Air Consumption	4.3CFM (122.0 L/min)
Length	108mm (4.3in.)
Net Weight	1.42kg [3.12lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

6320



1/2" Air Impact Wrench

Free Speed	9,500 RPM
Clutch	Jumbo Hammer
Working Torque (5s)	400Ft-lbs. (542Nm)
Max. Torque (15s)	700Ft-lbs. (949Nm)
Bolt Capacity	5/8" (16mm)
Ave. Air Consumption	4.3CFM (122.0 L/min)
Length	104mm (4.1in.)
Net Weight	1.45kg [3.2lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

6318



1/2" Air Impact Wrench

Free Speed	10,000 RPM
Clutch	Twin Hammer
Working Torque (5s)	450Ft-lbs. (610Nm)
Max. Torque (15s)	750Ft-lbs. (1,016Nm)
Bolt Capacity	5/8" (16mm)
Ave. Air Consumption	4.3CFM (122.0 L/min)
Length	113mm (4.5in.)
Net Weight	1.5kg [3.3lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

6321



1/2" Air Impact Wrench

Free Speed	10,000 RPM
Clutch	Jumbo Hammer
Working Torque (5s)	400Ft-lbs. (542Nm)
Max. Torque (15s)	700Ft-lbs. (949Nm)
Bolt Capacity	5/8" (16mm)
Ave. Air Consumption	5CFM (141.6 L/min)
Length	104mm (4.1in.)
Net Weight	1.38kg [3.04lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]