

Reversible Air Screwdriver

Ideal for nut tightening work of sheet metal and vehicle

Reversible Air Screwdriver

Ideal for nut tightening work of sheet metal and vehicle

1510



1/4" Reversible Straight Air Screwdriver

Free Speed	11,000 RPM
Clutch	Double Hammer
Max. Torque	7-30Ft-lbs. (9-41Nm)
Bolt Capacity	3/16" (5mm)
Ave. Air Consumption	1.2CFM (34.0 L/min)
Length	187mm (7.4in.)
Net Weight	0.8kg [1.8lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1810



1/4" Reversible Straight Air Screwdriver

Free Speed	9,000 RPM
Clutch	Double Hammer
Max. Torque	12-45Ft-lbs. (16-61Nm)
Bolt Capacity	1/4"-5/16" (6-8mm)
Ave. Air Consumption	1.5 CFM (42.5 L/min)
Length	215mm (8.5in.)
Net Weight	1.1kg [2.4lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1520



1/4" Reversible Angle Air Screwdriver

Free Speed	9,000 RPM
Clutch	Double Hammer
Max. Torque	7-30Ft-lbs. (9-41Nm)
Bolt Capacity	3/16" (5mm)
Ave. Air Consumption	1.2CFM (34.0 L/min)
Length	193mm (7.6in.)
Net Weight	1.1kg [2.4lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1820



1/4" Reversible Angle Air Screwdriver

Free Speed	7,200 RPM
Clutch	Double Hammer
Max. Torque	9-45Ft-lbs. (12-61Nm)
Bolt Capacity	1/4"-5/16" (6-8mm)
Ave. Air Consumption	1.2CFM (34.0 L/min)
Length	275mm (11.0in.)
Net Weight	1.5kg [3.3lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1811



1/4" Reversible Straight Air Screwdriver

Free Speed	9,500 RPM
Clutch	Double Hammer
Max. Torque	12-45Ft-lbs. (16-61Nm)
Bolt Capacity	1/4"- 5/16" (6-8mm)
Ave. Air Consumption	1.5CFM (42.5 L/min)
Length	205mm (8.1in.)
Net Weight	1kg [2.2lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1910



1/4" Reversible Straight Air Screwdriver

Free Speed	10,000 RPM
Clutch	Pinless Hammer
Max. Torque	16-52Ft-lbs. (21-70Nm)
Bolt Capacity	1/4"- 11/32" (6-9mm)
Ave. Air Consumption	1.5CFM (42.5 L/min)
Length	230mm (9.1in.)
Net Weight	1.1kg [2.4lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1532



1/4" Reversible Air Screwdriver

Free Speed	12,000 RPM
Clutch	Double Hammer
Max. Torque	7-30Ft-lbs. (9-41Nm)
Bolt Capacity	5/32-3/16" (4-5mm)
Ave. Air Consumption	1.2CFM (34.0 L/min)
Length	140mm (5.5in.)
Net Weight	1kg [2.2lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1832



1/4" Reversible Air Screwdriver

Free Speed	10,000 RPM
Clutch	Double Hammer
Max. Torque	12-45Ft-lbs. (16-61Nm)
Bolt Capacity	1/4"-5/16" (6-8mm)
Ave. Air Consumption	1.5CFM (42.5 L/min)
Length	180mm (7.1in.)
Net Weight	1.2kg [2.6lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]