

Air Random Orbital Sander

Designed for sanding feather edging and metal finish

Air Random Orbital Sander

Designed for sanding feather edging and metal finish

8003N



3" Air Random Orbital Sander (Non-Vacuum)

Free Speed	12,000 RPM
Pad Size	75mm / 3"
Orbit Diameter	2.5mm or 5mm / 3/32" or 3/16"
Spindle Thread Size	5/16"-24UNF
Ave. Air Consumption	2.5CFM (70.8 L/min)
Length	120mm (4.7in.)
Net Weight	0.7kg [1.5lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

8001



1-1/2" Air Random Orbital Sander

Free Speed	5,000 RPM / 7,500RPM
Pad Size	36mm / 1-1/2"
Orbit Diameter	2.5mm or 5mm / 3/32" or 3/16"
Spindle Thread Size	5/16"-24UNF
Ave. Air Consumption	2.5 CFM (70.8 L/min)
Length	120mm (4.7in.)
Net Weight	0.7kg [1.5lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

8003C



3" Air Random Orbital Sander (Central-Vacuum)

Free Speed	12,000 RPM
Pad Size	75mm / 3"
Orbit Diameter	2.5mm or 5mm / 3/32" or 3/16"
Spindle Thread Size	5/16"-24UNF
Ave. Air Consumption	2.5CFM (70.8 L/min)
Length	180mm (7.1in.)
Net Weight	0.8kg [1.8lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

8004



3" Air Random Orbital Buffer

Free Speed	12,000 RPM
Pad Size	75mm / 3"
Orbit Diameter	15mm / 9/16"
Spindle Thread Size	5/16"-24UNF
Ave. Air Consumption	2.5CFM (70.8 L/min)
Length	120mm (4.7in.)
Net Weight	0.8kg [1.8lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

8003S



3" Air Random Orbital Sander (Self-Vacuum)

Free Speed	12,000 RPM
Pad Size	75mm / 3"
Orbit Diameter	2.5mm or 5mm / 3/32" or 3/16"
Spindle Thread Size	5/16"-24UNF
Ave. Air Consumption	2.5CFM (70.8 L/min)
Length	180mm (7.1in.)
Net Weight	0.8kg [1.8lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

8007



Air Random Orbital Jitterbug Sander

Free Speed	10,000 RPM
Pad Size	75mmx100mm
Orbit Diameter	2.5mm / 3/32"
Ave. Air Consumption	3CFM (85.0 L/min)
Length	145mm (5.7in.)
Net Weight	0.8kg [1.8lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]