

Reversible Air Shut Off Screwdriver

Ideal for assembly application and carpentry

Reversible Air Screwdriver

Ideal for sheet metal, self tapping and wood screws

1310



1/4" Reversible Air Shut Off Screwdriver

Free Speed	2,300 RPM
Torque Range	3.5-8.8in-lbs. (0.4-1Nm)
Bolt Capacity	1/8" (3mm)
Ave. Air Consumption	1CFM (28.32L/min)
Length	187mm (7.4in.)
Net Weight	0.5kg [1.1lbs.]
Air Inlet	1/4"
Air Pressure	85PSI [6kg/cm ²]

1311



1/4" Reversible Air Shut Off Screwdriver

Free Speed	1,700 RPM
Torque Range	6.2-13.2in-lbs. (0.7-1.5Nm)
Bolt Capacity	9/64" (3.5mm)
Ave. Air Consumption	1CFM (28.32L/min)
Length	187mm (7.4in.)
Net Weight	0.5kg [1.1lbs.]
Air Inlet	1/4"
Air Pressure	85PSI [6kg/cm ²]

1410



1/4" Reversible Air Shut Off Screwdriver

Free Speed	1,100 RPM
Torque Range	9.7-18.5in-lbs. (1.1-2.1Nm)
Bolt Capacity	5/32" (4mm)
Ave. Air Consumption	1CFM (28.32L/min)
Length	187mm (7.4in.)
Net Weight	0.5kg [1.1lbs.]
Air Inlet	1/4"
Air Pressure	85PSI [6kg/cm ²]

1530



1/4" Reversible Air Screwdriver Internal Adjustable Clutch

Free Speed	1,800 RPM
Speed Reducer	3 gear, planetary
Torque Range	45-115in-lbs. (5.09-13Nm)
Bolt Capacity	5/32"-3/16" (4-5mm)
Ave. Air Consumption	4CFM (113.3 L/min)
Length	210mm (8.3in.)
Net Weight	1.1kg [2.4lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1631



1/4" Reversible Air Screwdriver Internal Adjustable Clutch

Free Speed	800 RPM
Speed Reducer	3 gear, planetary
Torque Range	45-145in-lbs. (5.09-16.39Nm)
Bolt Capacity	1/4" (6mm)
Ave. Air Consumption	4CFM (113.3 L/min)
Length	230mm (9.1in.)
Net Weight	1.3kg [2.9lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1530E



1/4" Reversible Air Screwdriver External Adjustable Clutch

Free Speed	1,800 RPM
Speed Reducer	3 gear, planetary
Torque Range	45-115in-lbs. (5.09-13Nm)
Bolt Capacity	5/32"-3/16" (4-5mm)
Ave. Air Consumption	4CFM (113.3 L/min)
Length	210mm (8.3in.)
Net Weight	1.1kg [2.4lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1631E



1/4" Reversible Air Screwdriver External Adjustable Clutch

Free Speed	800 RPM
Speed Reducer	3 gear, planetary
Torque Range	45-145in-lbs. (5.09-16.39Nm)
Bolt Capacity	1/4" (6mm)
Ave. Air Consumption	4CFM (113.3 L/min)
Length	230mm (9.1in.)
Net Weight	1.3kg [2.9lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]