

Air Valve Lapper

Renovating the valves of cylinder in the engine

Air Reciprocating Saw

Designed for cutting tasks of aluminum and steel

2500



Air Valve Lapper

Blows Per Minute	5,600 BPM
Ave. Air Consumption	2.5CFM (70.8 L/min)
Length	230mm (9.1in.)
Net Weight	1.5kg [3.3lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

7600



Air Reciprocating Saw

Strokes Per Minute	10,000 SPM
Piston Stroke Length	10mm
Capacity of Cutting	1.6mm
Ave. Air Consumption	3.5CFM (99.12 L/min)
Length	235mm (9.3in.)
Net Weight	1kg [2.2lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

7601



Air Reciprocating Saw

Strokes Per Minute	9,000 SPM
Piston Stroke Length	10mm
Capacity of Cutting	1.6mm
Ave. Air Consumption	3.5CFM (99.12 L/min)
Length	258mm (10.2in.)
Net Weight	1kg [2.2lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

7603



Air Reciprocating Saw

Strokes Per Minute	5,000 SPM
Piston Stroke Length	10mm
Capacity of Cutting	1.6mm
Ave. Air Consumption	4CFM (113.3 L/min)
Length	250mm (9.8in.)
Net Weight	1kg [2.2lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

7605



Air Reciprocating Saw Gear Driven

Strokes Per Minute	5,000 SPM
Stroke Length	8mm
Capacity of Cutting	9.5mm
Ave. Air Consumption	3.5CFM (99.12 L/min)
Length	270mm (10.6in.)
Net Weight	1.25kg [2.8lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

7604



Air Reciprocating Saw

Strokes Per Minute	7,000 SPM
Piston Stroke Length	5mm
Capacity of Cutting	1.6mm
Ave. Air Consumption	4CFM (113.3 L/min)
Length	200mm (7.9in.)
Net Weight	0.6kg [1.3lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

7606



Air Reciprocating Saw Gear Driven

Strokes Per Minute	7,000 SPM
Stroke Length	10mm
Capacity of Cutting	5mm
Ave. Air Consumption	4CFM (113.3 L/min)
Length	267mm (10.5in.)
Net Weight	0.95kg [2.1lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]