

Right Angle Air Drill

Designed for precise drilling in confined area

45 Degree Angle Air Drill

Designed for precise drilling in confined area

3830C



Right Angle Air Drill
0.3HP / 224W (Chuck Type)

Free Speed	4,000 RPM
Speed Reducer	2 gear, Caged
Chuck Size	1/8" (3mm)
Horse Power	0.3HP / 224W
Ave. Air Consumption	3CFM (85.0 L/min)
Length	240mm (9.5in.)
Net Weight	0.65kg [1.4lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3831C



Right Angle Air Drill, Extended
0.3HP / 224W (Chuck Type)

Free Speed	4,000 RPM
Speed Reducer	2 gear, Caged
Chuck Size	1/8" (3mm)
Horse Power	0.3HP / 224W
Ave. Air Consumption	3CFM (85.0 L/min)
Length	308mm (12.1in.)
Net Weight	0.75kg [1.7lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3832



45 Degree Angle Air Drill
0.3HP / 224W (Collet Type)

Free Speed	4,000 RPM
Speed Reducer	2 gear, Caged
Spindle Thread Size	9/32"-40UNS
Horse Power	0.3HP / 224W
Ave. Air Consumption	3CFM (85.0 L/min)
Length	256mm (10.1in.)
Net Weight	0.65kg [1.4lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3833



45 Degree Angle Air Drill, Extended
0.3HP / 224W (Collet Type)

Free Speed	4,000 RPM
Speed Reducer	2 gear, Caged
Spindle Thread Size	9/32"-40UNS
Horse Power	0.3HP / 224W
Ave. Air Consumption	3CFM (85.0 L/min)
Length	333mm (13.1in.)
Net Weight	0.75kg [1.7lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3850C



Right Angle Air Drill
0.5HP / 373W (Chuck Type)

Free Speed	3,600 RPM
Speed Reducer	2 gear, Caged
Chuck Size	1/8" (3mm)
Horse Power	0.5HP / 373W
Ave. Air Consumption	3.5CFM (99.12 L/min)
Length	259mm (10.2in.)
Net Weight	0.86kg [1.9lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3851C



Right Angle Air Drill, Extended
0.5HP / 373W (Chuck Type)

Free Speed	3,600 RPM
Speed Reducer	2 gear, Caged
Chuck Size	1/8" (3mm)
Horse Power	0.5HP / 373W
Ave. Air Consumption	3.5CFM (99.12 L/min)
Length	327mm (12.9in.)
Net Weight	1kg [2.2lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3852



45 Degree Angle Air Drill
0.5HP / 373W (Collet Type)

Free Speed	3,600 RPM
Speed Reducer	2 gear, Caged
Spindle Thread Size	9/32"-40UNS
Horse Power	0.5HP / 373W
Ave. Air Consumption	3.5CFM (99.12 L/min)
Length	274mm (10.8in.)
Net Weight	0.86kg [1.9lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3853



45 Degree Angle Air Drill, Extended
0.5HP / 373W (Collet Type)

Free Speed	3,600 RPM
Speed Reducer	2 gear, Caged
Spindle Thread Size	9/32"-40UNS
Horse Power	0.5HP / 373W
Ave. Air Consumption	3.5CFM (99.12 L/min)
Length	351mm (13.8in.)
Net Weight	1kg [2.2lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

45 Degree Angle Air Drill

Designed for precise drilling in confined area

45 Degree Angle Air Drill

Designed for precise drilling in confined area

3832T



45 Degree Angle Air Drill
0.3HP / 224W (Thread Type)

Free Speed	4,000 RPM
Speed Reducer	2 gear, Caged
Spindle Thread Size	1/4"-28UNF
Horse Power	0.3HP / 224W
Ave. Air Consumption	3CFM (85.0 L/min)
Length	256mm (10.1in.)
Net Weight	0.65kg [1.4lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3833T



45 Degree Angle Air Drill, Extended
0.3HP / 224W (Thread Type)

Free Speed	4,000 RPM
Speed Reducer	2 gear, Caged
Spindle Thread Size	1/4"-28UNF
Horse Power	0.3HP / 224W
Ave. Air Consumption	3CFM (85.0 L/min)
Length	333mm (13.1in.)
Net Weight	0.75kg [1.7lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3832C



45 Degree Angle Air Drill
0.3HP / 224W (Chuck Type)

Free Speed	4,000 RPM
Speed Reducer	2 gear, Caged
Chuck Size	1/8" (3mm)
Horse Power	0.3HP / 224W
Ave. Air Consumption	3CFM (85.0 L/min)
Length	256mm (10.1in.)
Net Weight	0.65kg [1.4lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3833C



45 Degree Angle Air Drill, Extended
0.3HP / 224W (Chuck Type)

Free Speed	4,000 RPM
Speed Reducer	2 gear, Caged
Chuck Size	1/8" (3mm)
Horse Power	0.3HP / 224W
Ave. Air Consumption	3CFM (85.0 L/min)
Length	333mm (13.1in.)
Net Weight	0.75kg [1.7lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3852T



45 Degree Angle Air Drill
0.5HP / 373W (Thread Type)

Free Speed	3,600 RPM
Speed Reducer	2 gear, Caged
Spindle Thread Size	1/4"-28UNF
Horse Power	0.5HP / 373W
Ave. Air Consumption	3.5CFM (99.12 L/min)
Length	274mm (10.8in.)
Net Weight	0.86kg [1.9lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3853T



45 Degree Angle Air Drill, Extended
0.5HP / 373W (Thread Type)

Free Speed	3,600 RPM
Speed Reducer	2 gear, Caged
Spindle Thread Size	1/4"-28UNF
Horse Power	0.5HP / 373W
Ave. Air Consumption	3.5CFM (99.12 L/min)
Length	351mm (13.8in.)
Net Weight	1kg [2.2lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3852C



45 Degree Angle Air Drill
0.5HP / 373W (Chuck Type)

Free Speed	3,600 RPM
Speed Reducer	2 gear, Caged
Chuck Size	1/8" (3mm)
Horse Power	0.5HP / 373W
Ave. Air Consumption	3.5CFM (99.12 L/min)
Length	274mm (10.8in.)
Net Weight	0.86kg [1.9lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

3853C



45 Degree Angle Air Drill, Extended
0.5HP / 373W (Chuck Type)

Free Speed	3,600 RPM
Speed Reducer	2 gear, Caged
Chuck Size	1/8" (3mm)
Horse Power	0.5HP / 373W
Ave. Air Consumption	3.5CFM (99.12 L/min)
Length	351mm (13.8in.)
Net Weight	1kg [2.2lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]