

Composite Air Impact Wrench

Compact, Light-Weight and Ergonomic

Composite Air Impact Wrench

Compact, Light-Weight and Ergonomic

66503L



3/4" Composite Air Impact Wrench, 3" Extended

Free Speed	5,500 RPM
Clutch	Twin Hammer
Working Torque (5s)	1,100Ft-lbs. (1,491Nm)
Max. Torque (15s)	1,400Ft-lbs. (1,897Nm)
Bolt Capacity	1-1/8" (29mm)
Ave. Air Consumption	7CFM (198.3 L/min)
Length	296mm (11.7 in.)
Net Weight	4.2kg [9.2lbs.]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

66506L



3/4" Composite Air Impact Wrench, 6" Extended

Free Speed	5,500 RPM
Clutch	Twin Hammer
Working Torque (5s)	1,000Ft-lbs. (1,355Nm)
Max. Torque (15s)	1,300Ft-lbs. (1,762Nm)
Bolt Capacity	1-1/8" (29mm)
Ave. Air Consumption	7CFM (198 L/min)
Length	373mm (14.7 in.)
Net Weight	4.7kg [10.3lbs.]
Air Inlet	3/8"
Air Pressure	90PSI [6.3kg/cm ²]

66516L



1" Composite Air Impact Wrench, 6" Extended

Free Speed	5,500 RPM
Clutch	Twin Hammer
Working Torque (5s)	1,000Ft-lbs. (1,355Nm)
Max. Torque (15s)	1,300Ft-lbs. (1,762Nm)
Bolt Capacity	1-1/8" (29mm)
Ave. Air Consumption	7 CFM (198 L/min)
Length	383mm (15.1 in.)
Net Weight	5kg [10.1lbs.]
Air Inlet	3/8"
Air Pressure	90PSI [6.3kg/cm ²]

6152



1" Composite Air Impact Wrench

Free Speed	5,500 RPM
Clutch	Twin Hammer
Working Torque (5s)	2,000Ft-lbs. (2,710Nm)
Max. Torque (15s)	2,200Ft-lbs. (2,981Nm)
Bolt Capacity	1-3/4" (45mm)
Ave. Air Consumption	7.5CFM (212.4 L/min)
Length	256mm (10.1 in.)
Net Weight	5.9kg [13.0lbs.]
Air Inlet	1/2"
Air Pressure	90PSI [6.3kg/cm ²]

6150



1" Composite Air Impact Wrench

Free Speed	5,500 RPM
Clutch	Twin Hammer
Working Torque (5s)	2,000Ft-lbs. (2,710Nm)
Max. Torque (15s)	2,200Ft-lbs. (2,981Nm)
Bolt Capacity	1-3/4" (45mm)
Ave. Air Consumption	7.5CFM (212.4 L/min)
Length	425mm (16.7 in.)
Net Weight	6.2kg [13.7lbs.]
Air Inlet	1/2"
Air Pressure	90PSI [6.3kg/cm ²]

61526L



1" Composite Air Impact Wrench, 6" Extended

Free Speed	5,500 RPM
Clutch	Twin Hammer
Working Torque (5s)	2,000Ft-lbs. (2,710Nm)
Max. Torque (15s)	2,200Ft-lbs. (2,981Nm)
Bolt Capacity	1-3/4" (45mm)
Ave. Air Consumption	7.5CFM (212.4 L/min)
Length	417mm (16.4 in.)
Net Weight	6.8kg [15.0lbs.]
Air Inlet	1/2"
Air Pressure	90PSI [6.3kg/cm ²]

61508L



1" Composite Air Impact Wrench, 8" Extended

Free Speed	5,500 RPM
Clutch	Twin Hammer
Working Torque (5s)	2,000Ft-lbs. (2,710Nm)
Max. Torque (15s)	2,200Ft-lbs. (2,981Nm)
Bolt Capacity	1-3/4" (45mm)
Ave. Air Consumption	7.5CFM (212.4 L/min)
Length	635mm (25.0 in.)
Net Weight	7.5kg [16.5lbs.]
Air Inlet	1/2"
Air Pressure	90PSI [6.3kg/cm ²]